

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (as Used on Label and List)

ELM104-X1 Monitor Screen Cleaner

Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's name Sanus	Emergency Telephone Number (800) 359-5520
Address (Number, Street, City, State and ZIP Code) 2221 Highway 36 West St. Paul, MN 55113	Telephone Number for Information (651) 484-7988
	Date Prepared 5December2008
	Signature of Preparer (optional)

Section II—Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
N/A				

Section III—Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H ₂ O = 1)	N/A
Vapor Pressure (mm Hg)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	Complete		
Appearance and Odor	Clear liquid with fragrant odor		

Section IV—Fire and Explosion Hazard Data

Flash Point (Method Used) N/A	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media	Dry chemical, carbon dioxide, alcohol foam, water fog		
Special Fire Fighting Procedures	As in any fire, firefighters should wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear		
Unusual Fire and Explosion Hazards	Closed containers exposed to heat may rupture		

(Reproduce locally)

OSHA 174 Sept. 1985



Section V—Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	Direct sunlight, excessive heat and physical damage
Incompatibility (<i>Materials to Avoid</i>) Avoid contact with nitric acid, sulfuric acid, strong oxidizers. Avoid heat sparks, flame.			
Hazardous Decomposition or Byproducts N/A			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	N/A

Section VI—Health Hazard Data

Route(s) of Entry	Inhalation? X	Skin? X	Ingestion? X
Health Hazards (<i>Acute and Chronic</i>)			
Inhalation : Low hazard for recommended handling			
Eye: No specific hazard known. May cause transient irritation.			
Skin: low hazard for recommended handling.			
Ingestion: N/A			
Carcinogenicity N/A	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A

Signs and Symptoms of Exposure

Inhalation: Low concentrations may cause mild irritation of eyes, nose, and throat. High concentrations may result in headaches.

Skin Contact: Prolonged or repeated skin contact may result in irritation, drying, and cracking of the skin

Eye Contact: contact may cause irritation

Ingestion: Ingestion of large quantities may cause drowsiness, nausea, vomiting

Medical Conditions Generally Aggravated by Exposure

N/A

Emergency and First Aid Procedures

Inhalation: Remove person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical aid.

Skin Contact: Wash affected area with soap and water. If irritation persists, seek medical attention. Also remove contaminated clothing. Wash clothing before re-use.

Eye Contact: Wash eyes with plenty of water for at least 15 minutes, lifting lids occasionally to remove particles. Seek medical aid.

Ingestion: Induce vomiting if large quantities are swallowed. Get medical attention.

Section VII—Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled

Small spills: Flush into sewer with plenty of water. Otherwise, absorb with vermiculite or other inert material, and then place in container for chemical waste. Prevent spill from entering drinking water supplies or streams. Finish cleaning by spreading water on the contaminated surface. Eliminate all ignition sources. Any product recovery or disposal must comply with local, state, federal, or country specific regulations.

Waste Disposal Method

Discharge, treatment, or disposal is subject to national, state, provincial, or municipal laws. Consult state or local regulatory authorities before flushing to sewer with large amounts of water.

Precautions to Be Taken in Handling and Storing

Use when power off. Eye protection and protective clothing as necessary to prevent excessive contact is recommended.

Other Precautions

Storage: Store in cool, well ventilated area away from all sources of ignition and out of direct sunlight. Keep container tightly closed. Protect from physical damage. Minimize exposure to air. Avoid sparks, flames, and other ignition sources. Put it lightly when packing and transport, prevent the packing and container from damage. Keep out of reach of children and pets.

Section VII—Control Measures

Respiratory Protection (*Specify Type*)

Ventilation	Local Exhaust <input checked="" type="checkbox"/>	Special Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions.
	Mechanical (<i>General</i>)	Other

Protective Gloves	None should be needed in normal use.	Eye Protection	None should be needed in normal use.
-------------------	--------------------------------------	----------------	--------------------------------------

Other Protective Clothing or Equipment None should be needed in normal use.

Work/Hygienic Practices Wash thoroughly after handling and before eating, drinking, or smoking.
